

Straight Blade Devices

15A, 125V, 2 Pole, 3 Wire Grounding

Commercial Specification Grade Duplex Receptacles for Controlled Applications

HUBBELL

Features

- Permanently marked with universal power symbol and the word "CONTROLLED" to visually identify receptacles used in automatic energy management systems
- Patented TR design eliminates plug-in difficulty and TR complaints
- Markings can be read regardless of mounting orientation
- Complies with NEC Section 406.3, ASHRAE 90.1, and California Title 24 requirements
- Complements Hubbell's Load Logic control system or other available energy management system



Ordering Information

| Description | Device Color | UPC Number | Catalog Number |
|----------------------------------|--------------|--------------|----------------|
| Smooth face, back and side wired | Ivory | 783585582450 | BR15C11TR |

Listings

Fed. Spec. W-C-596
UL Listed to UL498 File No. E2186
Certified to CSA, C22.2, No. 42
NEMA® WD-6 Compliant

Online Resources

[eCatalog](#)

Specifications

| | |
|---------------------------------|------------------------------------|
| Ground Contacts | Brass |
| Mounting Strap | .040 in. Galvanized steel |
| Face | Nylon |
| Automatic Self-grounding Staple | Stainless steel |
| Mounting Screws | Galvanized Steel |
| Base | Nylon |
| Power Contacts | .030 in. (.8) Brass |
| Wire Clamp | .062 in. (1.6) Nickel plated steel |

Performance

Electrical

| | |
|----------------------|--|
| Current Interrupting | Certified for current interrupting at full rated current |
| Dielectric Voltage | Withstands 2,000V minimum |

Mechanical

| | |
|-------------------------|--|
| Product Identification | Ratings are a permanent part of the device |
| Terminal Accommodation | #14-10 AWG stranded or solid copper wire only. |
| Terminal Identification | Terminals identified in accordance with UL 498 and CSA |

Environmental

| | |
|-----------------------|---|
| Flammability | UL 94V-2 |
| Operating Temperature | Maximum continuous 75°C; minimum -40°C (w/o impact) |

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

