

SRSA2
DECORATIVE AND POST TOP

FEATURES

- TiR Optics
- Patented low profile luminaire
- Available in 580nm, 3000K, 4000K and 5000K standard CCT
- Type 1, 2, 3, 4W, 5QM, 5W distributions
- 0 - 10V dimming drivers standard
- IP66 optic assembly



Solitaire®



RELATED PRODUCTS

[Intent](#)

[KFL](#)

[LTV8](#)

SPECIFICATIONS

CONSTRUCTION

- One piece non die-cast housing, low copper (<0.6% Cu) Aluminum Alloy with integral cooling ribs over the optical chamber and electrical compartment
- All hardware is stainless steel or electro-zinc plated steel
- Finish: fade and abrasion resistant, electrostatically applied, thermally cured, triglycidal isocyanurate (TGIC) polyester powdercoat
- One-piece die-cast, low copper (<0.6% Cu) aluminum alloy lens frame.
- Silicone gaskets seal the compartments at the barrier surface.

INSTALLATION

- Fixtures must be grounded in accordance with national, state and/or local electrical codes. Failure to do so may result in serious personal injury

OPTICS

- Optical cartridge system consisting of a die cast heat sink, LED engine, TIR optics, gasket and bezel plate
- Cartridge is easily disassembled to replace components. Optics are held in place without the use of adhesives
- Molded silicone gasket ensures a weatherproof seal around each individual LED

OPTICS (CONTINUED)

- Features revolutionary individual LED optical control based on high performance TIR optical designs
- Clear Acrylic lens is standard
- Optional BackLight Control for complete control of unwanted backlight
- IP66 Optical assembly
- Type 1, 2, 3, 4W, 5QM, and 5W standard distributions. Custom available
- Amber, 3000K, 4000K, 5000K standard CCT. Custom available
- Die-cast, low copper aluminum heat sink modules provide thermal transfer at PCB level
- Anodized aluminum heat sink modules

ELECTRICAL

- Dimming range from 10% to 100% through the use of standard 0-10V interface on the programmable driver
- Modular wiring harness in the service area provides user access to the dimming circuitry
- Optional factory programmed dimming profile
- Surge protection: 10kV surge suppression
- SF for 120, 277, 347 Line volts
DF for 208, 240, 480 Line volts
- Wiring: 14GA wires rated 150°C

CONTROLS

- Optional PC 7 Pin Receptacle 7-pin construction allows for a user-defined interface and provides a controlled definition of operational performance. ANSI twist-lock control module by-others
- Button Photocell
- Consult factory for additional sensors.

CERTIFICATIONS AND LISTINGS

- Listed to UL1598 and CSA C22.2#250.0-24 for wet locations
- RoHS compliant

WARRANTY

- 5 year warranty
- See [HLI Standard Warranty](#) for additional information

KEY DATA	
Lumen Range	3155–15616
Wattage Range	58.31–135.6
Efficacy Range (LPW)	49.9–124.8
Reported Life (Hours)	L70/60,000
Weight	45 lbs / 20.41 kg
EPS Front View / Side View	1.5

ORDERING GUIDE

Example: SRSA2-72L-600-3K7-3-CP-UNV-BLT-PC- 3.5

CATALOG #

Solitaire		Mounting		Engine		CCT/CRI		Distribution		Lens	
SRSA2	Solitaire 2.0	1SA	Single Arm Mount	72L-260	72L - 260mA-6000lm	AM	Amber-595nm Peak ¹	1	Type I	CP	Clear Lexan
		1W	Wall Mount	72L-400	72L - 400mA-9000lm	3K7	3000K, 70 CRI	2	Type II	WA	White Acrylic ²
				72L-600	72L - 600mA-14000lm	4K7	4000K, 70 CRI	3	Type III		
						5K7	5000K, 70 CRI	4W	Type IV Wide		
								5QM	Type V Square Medium		
								5W	Type V Wide (Round)		

Voltage		Fixture Finish		Option		Pole Shape/Cross Section	
UNV	120-277V	BLS	Black Gloss Smooth	7PR	7-pin Receptacle	SQ	Square
347	347V	BLT	Black Matte Textured	BC	Backlight Control	2.4	2.4" OD
480	480V	DBS	Dark Bronze Gloss Smooth	PC	Button Photocell	3.00	3.00" OD
		DBT	Dark Bronze Matte Textured	SF	Single Fuse for 120, 277, 347 Line volts	3.25	3.25" OD
		GTT	Graphite Matte Textured	DF	Double Fuse for 208, 240, 480 Line volts	3.50	3.50" OD
		LGS	Light Grey Gloss Smooth			3.75	3.75" OD
		LGT	Light Grey Matte Textured			4.00	4.00" OD
		PSS	Platinum Silver Gloss Smooth			4.50	4.50" OD
		VGT	Verde Green Matte Textured			5.00	5.00" OD
		WHS	White Gloss Smooth			6.00	6.00" OD
		WHT	White Matte Textured			HA Arm	HA Arm
		Color Option					
		CC ³	Custom Color				

Notes:

- 1 Turtle friendly
- 2 Only available with Type 3 and Type 5 Distributions
- 3 Consult factory for custom color, marine and corrosive finish options

SRSA2



DECORATIVE AND POST TOP

PRODUCT EXCEPTIONS & DETAILS

CONTROLS

7PR

- Fully gasketed and wired 7-pin receptacle option. Easy access location above the electrical compartment. 7-pin construction allows for a user-defined interface and provides a controlled definition of operational performance. ANSI twist-lock control module by-others.
- Standard customer operation modes:
 1. Traditional on/off photoelectric control.
 2. 5-pin wireless photoelectric control for added dimming feature.
 3. 7-pin wireless photoelectric control for dimming and additional I/O connections for customer use.



DIMMING:

- Dimming range from 100% to 10% through the use of the standard 0-10V interface on the programmable driver.
- Modular wiring harness in the service area provides user access to the dimming circuitry.
- Dimming circuitry compatible with 0-10V, user-defined control devices.
- Optional factory programmed dimming profile.

ASTRODIM

- AstroDIM provides multi-stage night-time power reduction based on an internal timer referenced to the power on/off time. There is no need for an external control infrastructure. The unit automatically performs a dimming profile based on the predefined scheduled reference to the midpoint, which is calculated based on the power on/off times. Please contact factory for feasibility.

OPTIONAL FUSING:

- SF for 120, 277, and 347 Line volts
- DF for 208, 240, and 480 Line volts
- High temperature fuse holders factory installed inside the fixture housing.
- Fuse is included.

CAUTION:

- Fixtures must be grounded in accordance with national, state and/or local electrical codes. Failure to do so may result in serious personal injury.

SRSA2




DECORATIVE AND POST TOP

PRODUCT EXCEPTIONS & DETAILS (CONTINUED)




ARM OPTIONS

- Refer to Kim Lighting's Arms and Poles Specification Guide for EPA information and additional information on arm, tenon and wall mounting. 1W Wall
- Mount arm is not included and must be ordered separately.




Side Mount Swept Cast Arm

ARM	Tenon Mount	Wall Mt
		
HA11S	HA11S-TM1 HA11S-TM2 HA11S-TM3 HA11S-TM4	HA11S-W
Mounting:	1SA 2SB 3SY 4SC	




Side Pole S-Shaped Up Cast Arm

ARM	Tenon Mount	Wall Mt
		
HA12S	HA12S-TM1 HA12S-TM2 HA12S-TM3 HA12S-TM4	HA12S-W
Mounting:	1SA 2SB 3SY 4SC	




Side Pole S-Shaped Down Cast Arm

ARM	Tenon Mount	Wall Mt
		
HA13S	HA13S-TM1 HA13S-TM2 HA13S-TM3 HA13S-TM4	HA13S-W
Mounting:	1SA 2SB 3SY 4SC	


Side Pole Ribbon Arm w/ Bottom Scroll


ARM	Tenon Mount	Wall Mt
		
HA32S	HA32S-TM1 HA32S-TM2 HA32S-TM3 HA32S-TM4	HA32S-W
Mounting:	1SA 2SB 3SY 4SC	

Side Pole Ribbon Arm w/ Bottom Gusset

ARM	Tenon Mount	Wall Mt
		
HA34S	HA34S-TM1 HA34S-TM2 HA34S-TM3 HA34S-TM4	HA34S-W
Mounting:	1SA 2SB 3SY 4SC	

Side Pole Ribbon Arm w/ Bottom Brace

ARM	Tenon Mount	Wall Mt
		
HA36S	HA36S-TM1 Consult Factory	HA36S-W Consult Factory
Mounting:	1SA 2SB 3SY 4SC	



DELIVERED LUMENS

STANDARD CLEAR ACRYLIC LENS

LED #	Nominal Lumen Package	Drive Current	Distribution	3000K 70CRI					4000K 70CRI					5000K 70CRI				
				Lumen	BUG Rating			lm/w	Lumen	BUG Rating			lm/w	Lumen	BUG Rating			lm/w
					B	U	G			B	U	G			B	U	G	
72L	6,000	260	FR	6313	1	3	1	108.3	6487	1	3	1	111.2	7271	1	3	1	124.7
			FR-BC	3851	0	3	1	66.0	3957	0	3	1	67.9	4436	0	3	1	76.1
			2	6089	1	3	1	104.4	6256	1	3	1	107.3	7013	1	3	1	120.3
			2-BC	3221	0	3	1	55.2	3310	0	3	1	56.8	3710	0	3	1	63.6
			3	6206	1	3	2	106.4	6378	1	3	2	109.4	7149	1	3	2	122.6
			3-BC	3155	0	3	1	54.1	3242	0	3	1	55.6	3634	0	3	1	62.3
			4W	5812	1	3	2	99.7	5972	1	3	2	102.4	6694	1	3	2	114.8
			4W-BC	3314	0	3	1	56.8	3405	0	3	1	58.4	3817	0	3	1	65.5
			5QM	6148	2	3	1	105.4	6318	2	3	1	108.4	7082	2	3	1	121.5
	5W	6320	3	3	1	108.4	6494	3	3	1	111.4	7279	3	3	1	124.8		
	9,000	400	FR	9284	1	3	2	101.5	9540	1	3	2	104.3	10694	2	4	2	116.9
			FR-BC	5664	1	3	1	61.9	5820	1	3	1	63.6	6524	1	3	1	71.3
			2	8954	2	3	2	97.9	9201	2	3	2	100.6	10314	2	3	2	112.8
			2-BC	4737	0	3	1	51.8	4867	1	3	1	53.2	5456	1	3	1	59.7
			3	9128	2	3	2	99.8	9379	2	3	2	102.6	10514	2	3	2	115.0
			3-BC	4640	0	3	1	50.7	4768	0	3	1	52.1	5344	1	3	1	58.4
			4W	8547	1	3	2	93.5	8783	1	3	2	96.0	9845	2	3	2	107.7
			4W-BC	4873	1	3	2	53.3	5008	1	3	2	54.8	5613	1	3	2	61.4
			5QM	9042	3	3	1	98.9	9292	3	3	1	101.6	10415	3	3	1	113.9
	5W	9294	3	3	2	101.6	9551	3	3	2	104.4	10706	3	3	2	117.1		
	14,000	600	FR	13541	2	4	2	99.8	13915	2	4	2	102.6	15598	2	4	2	114.8
			FR-BC	8261	1	3	2	60.9	8489	1	3	2	62.6	9516	1	3	2	70.3
			2	13061	2	3	2	96.3	13421	2	3	2	99.0	15044	2	3	2	110.8
			2-BC	6909	1	3	1	50.9	7099	1	3	1	52.3	7958	1	3	1	58.8
			3	13314	2	3	2	98.3	13681	2	3	2	100.9	15336	2	3	2	112.4
			3-BC	6768	1	3	2	49.9	6954	1	3	2	51.3	7796	1	3	2	57.6
			4W	12467	2	3	3	91.9	12811	2	3	3	94.5	14360	2	3	3	105.8
			4W-BC	7108	1	3	2	52.4	7304	1	3	2	53.9	8188	1	3	2	60.6
5QM			13189	3	3	2	97.3	13553	3	3	2	99.9	15192	4	3	2	112.0	
5W	13557	4	3	2	100.0	13931	4	3	2	102.7	15616	4	3	2	115.1			

CRI Lumen Multiplier		
CCT	80 CRI	90 CRI
3000K	0.9119	0.7033
4000K	0.8941	N/A

Amber	
CCT	Multiplier
5000K	1
AM	0.1727

2700K Multiplier	
CCT	Multiplier
5000K	1
2700K	0.897

DELIVERED LUMENS (CONTINUED)

CP (CLEAR POLYCARBONATE) LENS

LED #	Nominal Lumen Package	Drive Current	Distribution	3000K 70CRI					4000K 70CRI					5000K 70CRI				
				Lumen	BUG Rating			lm/w	Lumen	BUG Rating			lm/w	Lumen	BUG Rating			lm/w
					B	U	G			B	U	G			B	U	G	
72L	6,000	260	FR	5819	1	3	1	99.8	5979	1	3	1	102.5	6703	1	3	1	114.9
			FR-BC	3550	0	3	1	60.9	3648	0	3	1	62.6	4089	0	3	1	70.1
			2	5612	1	3	1	96.3	5767	1	3	1	98.9	6465	1	3	1	110.9
			2-BC	2969	0	3	1	50.9	3051	0	3	1	52.3	3420	0	3	1	58.6
			3	5721	1	3	1	98.1	5879	1	3	1	100.8	6590	1	3	2	113.0
			3-BC	2908	0	3	1	49.9	2988	0	3	1	51.3	3350	0	3	1	57.4
			4W	5357	1	3	2	91.9	5505	1	3	2	94.4	6171	1	3	2	105.8
			4W-BC	3055	0	3	1	52.4	3139	0	3	1	53.8	3518	0	3	1	60.3
			5QM	5668	2	3	1	97.2	5824	2	3	1	99.9	6528	2	3	1	112.0
	5W	5826	3	3	1	99.9	5986	3	3	1	102.7	6710	3	3	1	115.1		
	9,000	400	FR	8558	1	3	2	93.6	8794	1	3	2	96.2	9857	1	3	2	107.8
			FR-BC	5221	0	3	1	57.1	5365	1	3	1	58.7	6014	1	3	1	65.8
			2	8254	1	3	1	90.3	8482	1	3	1	92.7	9508	2	3	2	104.0
			2-BC	4366	0	3	1	47.7	4487	0	3	1	49.1	5029	1	3	1	55.0
			3	8414	2	3	2	92.0	8646	2	3	2	94.5	9692	2	3	2	106.0
			3-BC	4277	0	3	1	46.8	4395	0	3	1	48.1	4927	1	3	1	53.9
			4W	7879	1	3	2	86.2	8096	1	3	2	88.5	9075	1	3	2	99.2
			4W-BC	4492	1	3	1	49.1	4616	1	3	1	50.5	5174	1	3	2	56.6
			5QM	8335	3	3	1	91.1	8565	3	3	1	93.7	9601	3	3	1	105.0
	5W	8568	3	3	2	93.7	8804	3	3	2	96.3	9869	3	3	2	107.9		
	14,000	600	FR	12483	2	4	2	92.1	12827	2	4	2	94.6	14378	2	4	2	106.0
			FR-BC	7615	1	3	2	56.2	7825	1	3	2	57.7	8772	1	3	2	64.7
			2	12040	2	3	2	88.8	12372	2	3	2	91.2	13868	2	3	2	102.3
			2-BC	6369	1	3	1	47.0	6544	1	3	1	48.3	7336	1	3	1	54.1
			3	12273	2	3	2	90.5	12611	2	3	2	93.0	14136	2	3	2	104.2
			3-BC	6239	1	3	2	46.0	6411	1	3	2	47.3	7186	1	3	2	53.0
			4W	11492	2	3	2	84.7	11809	2	3	2	87.1	13237	2	3	3	97.6
			4W-BC	6553	1	3	2	48.3	6733	1	3	2	49.7	7548	1	3	2	55.7
			5QM	12158	3	3	2	89.7	12493	3	3	2	92.1	14004	3	3	2	103.3
	5W	12497	4	3	2	92.2	12842	4	3	2	94.7	14395	4	3	2	106.2		


WA (WHITE ACRYLIC) LENS

LED #	Nominal Lumen Package	Drive Current	Distribution	3000K 70CRI					4000K 70CRI					5000K 70CRI				
				Lumen	BUG Rating			lm/w	Lumen	BUG Rating			lm/w	Lumen	BUG Rating			lm/w
					B	U	G			B	U	G			B	U	G	
72L	6,000	260	3	4538	1	3	3	77.8	4663	1	3	3	80.0	5227	1	3	3	89.6
			5W	4621	2	3	2	79.3	4749	2	3	2	81.4	5323	2	3	3	91.3
	9,000	400	3	6674	2	3	3	73.0	6858	2	3	3	75.0	7688	2	3	3	84.1
			5W	6796	3	3	3	74.3	6984	3	3	3	76.4	7828	3	4	3	85.6
	14,000	600	3	9657	2	4	4	71.2	9924	2	4	4	73.2	11124	2	4	4	82.0
			5W	9992	3	4	3	73.7	10268	3	4	3	75.7	11509	3	4	4	84.6

SRSA2

DECORATIVE AND POST TOP

DIMENSIONS



FRONT VIEW

SRSA2

DECORATIVE AND POST TOP

PHOTOMETRY

SRS2-72L-600-4K7-1


LUMINAIRE DATA

Description	4000K, 70CRI
Delivered Lumens	13915
Watts	135.6
Efficacy	102.6
IES Type	I
BUG Rating	B2-U4-G2
Mounting Height	15 ft
Grid Scale	15 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	10,473	75.3%
Downward House Side	2,428	17.4%
Downward Total	12,901	92.7%
Upward Street Side	441	3.2%
Upward House Side	572	4.1%
Upward Total	1,013	7.3%
Total Flux	13,914	100.0%

ISOFOOT CANDLE PLOT



SRS2-72L-600-4K7-2


LUMINAIRE DATA

Description	4000K, 70CRI
Delivered Lumens	13422
Watts	135.6
Efficacy	99.0
IES Type	II
BUG Rating	B2-U3-G2
Mounting Height	15 ft
Grid Scale	15 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	10,073	75.0%
Downward House Side	2,693	20.1%
Downward Total	12,766	95.1%
Upward Street Side	284	2.1%
Upward House Side	372	2.8%
Upward Total	656	4.9%
Total Flux	13,422	100.0%

ISOFOOT CANDLE PLOT



SRS2-72L-600-4K7-3


LUMINAIRE DATA

Description	4000K, 70CRI
Delivered Lumens	13681
Watts	135.23
Efficacy	101.2
IES Type	III
BUG Rating	B2-U3-G2
Mounting Height	15 ft
Grid Scale	15 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	10,431	76.2%
Downward House Side	2,621	19.2%
Downward Total	13,052	95.4%
Upward Street Side	282	2.1%
Upward House Side	347	2.5%
Upward Total	629	4.6%
Total Flux	13,681	100.0%

ISOFOOT CANDLE PLOT



SRSA2

DECORATIVE AND POST TOP

PHOTOMETRY (CONTINUED)

SRS2-72L-600-4K7-4W


LUMINAIRE DATA

Description	4000K, 70CRI
Delivered Lumens	12810
Watts	135.6
Efficacy	94.5
IES Type	IV
BUG Rating	B2-U3-G3
Mounting Height	15 ft
Grid Scale	15 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	10,248	80.0%
Downward House Side	2,063	16.1%
Downward Total	12,311	96.1%
Upward Street Side	223	1.7%
Upward House Side	276	2.2%
Upward Total	499	3.9%
Total Flux	12,810	100.0%

ISOFOOT CANDLE PLOT



SRS2-72L-600-4K7-5Q


LUMINAIRE DATA

Description	4000K, 70CRI
Delivered Lumens	13554
Watts	135.6
Efficacy	100.0
IES Type	VQ
BUG Rating	B3-U3-G2
Mounting Height	15 ft
Grid Scale	15 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	6,506	48.0%
Downward House Side	6,506	48.0%
Downward Total	13,012	96.0%
Upward Street Side	271	2.0%
Upward House Side	271	2.0%
Upward Total	542	4.0%
Total Flux	13,554	100.0%

ISOFOOT CANDLE PLOT



SRS2-72L-600-4K7-5W


LUMINAIRE DATA

Description	4000K, 70CRI
Delivered Lumens	13931
Watts	135.6
Efficacy	102.7
IES Type	VW
BUG Rating	B4-U3-G2
Mounting Height	15 ft
Grid Scale	15 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	6,716	48.2%
Downward House Side	6,716	48.2%
Downward Total	13,432	96.4%
Upward Street Side	250	1.8%
Upward House Side	250	1.8%
Upward Total	499	3.6%
Total Flux	13,931	100.0%

ISOFOOT CANDLE PLOT




SRSA2

DECORATIVE AND POST TOP

TM-30 DATA

COLOR VECTOR GRAPHIC




— Reference Illuminant — Test Source

TEST SOURCE

R _f	68
R _g	99
CCT(K)	3947
D _{uv}	0.0004
x	0.3831
y	0.3793
CIE R _a	72

SPECTRAL POWER DISTRIBUTION COMPARISON



ELECTRICAL DATA

LED #	System Watts	Current	Line Voltage		Amps AC						Min Power Factor	Max. THD (%)	Dimming				
			VAC	Hz	120	208	240	277	347	480			Dimming Range	Source Current Out		Absolute Voltage	
														Min	Max	Min	Max
72L	58.3	260 mA	120-480	50/60	0.49	0.28	0.24	0.21	0.17	0.12	>0.9	20	10% to 100%	0mA	1mA	0V	10V
	91.45	400 mA			0.76	0.44	0.38	0.33	0.26	0.19							
	135.6	600 mA			1.13	0.65	0.57	0.49	0.39	0.28							

TM-21 Lifetime Calculation - Projected Lumen Maintenance (25°C / 77°C)						
HOURS	0	25,000	36,000	50,000	100,000	Reported L70
Projected Lumen Maintenance	100%	92.5%	90.4%	87.7%	78.9%	>60000