

## Industrial Grade, Motor Disconnect, Unfused Switch, Non-Metallic Sloped Version Replacement Cover for 60A With inTOUCH Installation Free LED Phase Indication and Jog - HBLDS60 and HBLDS60T Series

By Hubbell Wiring Device-Kellems  
Catalog # [HBLDS60RCPJ](#)

Industrial Grade, Motor Disconnect, Unfused Switch, Non-Metallic Replacement Cover for 60A With inTOUCH Installation Free LED Phase Indication and Jog, HBLDS60 and HBLDS60T Series



### Features

- Constructed from corrosion and impact resistant UV stabilized non-metallic material
- Rounded sloped top enclosure supports best practices in hygienic design by shedding dirt and debris
- IP69k and Type 4X,12K water ingress protection
- Highly visible red handle can be locked in the OFF position as a method of compliance with OSHA Lockout/Tagout requirements
- Certified by NSF for hygiene in food processing applications
- Product rating are permanently laser-marked and will not wash off
- Six highly visible integral phase identification LEDs for use on 3 Phase Y or Delta systems provide secondary means of visual confirmation of make/break on all phases

### Application

Heavy Duty Industrial and/or Washdown

### Specifications

Industry Standard(s) cULus Listed  
Environmental Conditions Indoor and Outdoor

#### Material - Mounting Hardware

Type

Enclosure Type

Series

Specifications

Stainless Steel Screw Mounting

Accessories

IP69k and UL Type 4X, 12

Non-Fused

- Enclosure Gasket - Neoprene
- Handle - Valox®
- Shaft (Unfused) - Valox®
- Top - Valox®

783585763323

IP69k, NEMA Type 4X, 12

Replacement Cover

Gray

UPC

Ingress Protection

Style

Color

### Operational

Operating Cycles

Operating Temperature

10,000 Cycles Minimum

Without Impact Maximum

continuous 75°C and minimum -40 °C

### Product Assets

[Catalog Page \[English\]](#)

[Installation Manual \[English\]](#)

### General



A Hubbell brand