



PRIMARY LINES TO H1-H2-H3  
SECONDARY LINES TO X0-X1-X2-X3

NOTE: PRIMARY AND SECONDARY BUS AREA IN FRONT OF CASE.

**REVISIONS**

**NOTES:**

1. Dry Type
2. Class AA
3. Ventilated
4. Paint - #61 ANSI



KVA	CATALOG NUMBER	VOLTAGE		LUG KIT	WEIGHT	PHASE	FREQUENCY
		HIGH	LOW				
30	<b>T3030K0013BS</b>	480Δ	208Y/120		280 Lbs	3φ	60Hz
Temp Rise:	150°C	<b>TYPICAL PERFORMANCE DATA</b>				Typical Efficiency @ 35%	98.30%
Insulation:	220°C	Regulation @ 100% PF	2.60%	Windings:	AL	Typical No Load Losses:	100.70
NEMA ST20 Standard:	45 dB	Standards:	UL/CSA	Impedance:	4.46%	100% Load (Typ) Load Losses (I²R)	887.59
Electrostatic Shield:	Option	Approvals:	DOE-2016	Enclosure:	3R	Total Load Losses:	988.29

**Meets US DOE 2016 Efficiency**

DATE: 11-Jan-16

TYPE NO:

**CASE 1**